



TECHNICAL DATA SHEET

HW3004 Quadro

Design from Havwoods

USAGE: (SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR).



PRODUCT DETAILS

Product Code	HW3004
Product Range	Design from Havwoods
Construction	Engineered
Specie	European Oak
Pattern	Herringbone
Process	Sanded & Smoked
Finish	UV Oiled
Profile	Tongue & Groove
Edge Profile	4-Sided Bevelled Edge
Top Layer	4mm European Oak
Backing	Birch Plywood
Thickness	13mm
Width	120mm
Length	600mm
Pack Size	0.86m ²
Grade	Prime
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	Wet systems only*#

GRADING CRITERIA

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood defects and filler, if any at all. Where filler is used its colour is carefully selected to complement the wood rather than to match it exactly and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

TECHNICAL CRITERIA

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,360 lbf (6,000N)
Formaldehyde Emission	E1(EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip testing	65/39 PTV (BS7976-2:2002+A1:2013))
Reaction to Fire Certification	Cfl-s1 (EN 13501-1:2007)
Thermal Conductivity	λ 0.17 W/m K (EN 12664)

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

